

# S-LOK

## STANDING SEAM ROOF & WALL CLADDING

**S-LOK** is high tensile sheeting offers versatility, rigidity, strength and complete water seal installation. S-Lok provides a complete water proof as the joints being seam lock splashes.

### ADVANTAGES

#### COST SAVINGS

S-LOK is produced in three thickness so you can choose the one that suits your needs at least material cost. With its high strength and rigidity supports can be widely spaced to reduce under structure costs. Fixing is by the concealed fixing clip fastening method

#### PROTECTION

Colourstrong, PVF<sup>2</sup> and Galvalume coated steel provides the best protection from the enviroment and gives long to any building.

#### LONG SPANS

The profile has been designed so that a very strong section has been produced. This allows the use of wide support spacings while still being able to resist wind and other loads.

#### COVERAGE

Standard width of production is 390 mm. Formation of any customer specified width can be undertaken. Minimum width 300mm. Maximum width 863mm.

#### ROOF PITCH

Recommended minimum roof pitch is 1° for double lock standing seam. Recommended minimum roof pitch is 6° for dsingle lock standing seam.

#### LENGTHS

S-LOK can be factory rolled and cut to any customer specified length. Length is only restricted by transport limitations. For large quantity and longer lengths roll forming at site canbe undertaken with prior arrangements.



### SUPPORT RECOMMENDATIONS MAXIMUM SUPPORT SPACINGS(NON CYCLONIC)

Area	: Non-cyclonic
Max. Building Height	: 5m
Wind Velocity	: 50m/s
Internal Pressure Coefficient	: +/- 0.2
Terrain Category	: 3



### MAXIMUM SUPPORT SPACING (NON -CYCLONIC)

MATERIAL THICKNESS	ROOF SPANS					WALL SPANS			
	SINGLE	END	INTERNAL	OVERHANG		SINGLE	END	INTERNAL	OVERHANG
				UNSTIFFENED	STIFFENED				
0.42 BMT	1000	1300	1400	200	600	2200	2200	2400	300
0.48 BMT	1600	1900	2200	200	600	2300	2700	2900	400
0.57 BMT	2200	2400	2800	300	900	2600	2900	3000	600

**Interline (B) Sdn Bhd.**

Lot 56, 57, 58 & 59 Beribi Industrial Complex II BE 1118 Gadong, P.O. Box 520 Postal Code BE 3978 Bandar Seri Begawan - Brunei Darussalam

Telp (673) 2448721-24 Fax (673) 2448725 / (673) 8227788 - Whatsapp Only - Email : info@interline-asia.com